
TOWER 118.200

CHITA, RUSSIA

KADALA



Not to scale

APRON:

 OLD apron-western part of the Terminal (stands 1-16) Surface: Cement-Concrete Strength: PCN 26/R/B/W/T

2. NEW apron-eastern part of the Terminal (stands A, B, C)

Surface: Cement-Concrete Strength: PCN 39/R/A/W/T

3. Apron domestic flight-western part of the Terminal

(stands 1B, 2B, 17-20) Surface: Asphalt-Concrete Strength: PCN 14/F/B/Y/T

TAXIWAYS:

Width: 1, 4, 6-8 - 23m

3, 5 - 14m

12 - 7m

Surface: 1, 4, 6-8 - Cement-Concrete

5, 12 - Asphalt-Concrete

Strength: 1, 4, 6-8 - PCN 51/R/B/W/T

3 - PCN 30/R/B/W/T 5, 12 - PCN 14/F/B/Y/T

WARNING:

- Turning on the end segment of RWY 29 shall be carried out with increased caution, at reduced speed with a slight braking. If unable to carry out the turn under these conditions, the flight crew shall carry out turning under assistance of a tow tractor.
- 2. Taxiing of ACFT from stands A, B, 1-6 shall be carried out at derating power of engines. If unable to taxi from the stands under own engines power, the aircraft shall be towed to the marked start-up positions 1 and 2. Start-up position 1 is on TWY 7. Start-up position 2 is on TWY 6 between TWY 7 and TWY 8.
- 3. There is an obstacle (TWR) north of TWY 6 between TWY 5 and TWY 7. The distance between TWY 6 centre line and the obstacle is 30m.
- 4. TWY 4 is AVBL for index 5 ACFT. TWY 3 is AVBL for index 3 ACFT (in the daylight hours). TWY 5 and TWY 12 are AVBL for index 1 ACFT (in the daylight hours).
- 5. It is prohibited for index 6 ACFT to taxi from stand A under own engines power, when stands 2, 3, 3A are occupied. It is prohibited for index 6 ACFT to taxi from stand B under own engines power, when stands 3, 3A are occupied.

A, B, C, 1-6	Tu-154B, Tu-154M, B737-200, B737-300, B737-400, B737-700, B737-800, A-319, A-320 and their modifications, CRJ-100 and its modifications
A, B, C	II-62 and its modifications, II-76 and its modifications, Tu-204, Tu-204-100, Tu-204C, Tu-214 and its modifications, B757-200, B767 and its modifications, A-310, A-321 and their modifications, MD-82, Mi-26
1-6	An-12, An-140, An-148, II-18, II-114, Tu-134 and its modifications, Yak-40, Yak-42, ATR-42, Dash-8,

ACFT types:

1-6, 1B, 2B, 7-16 An-24, An-26, L-410

1-6, 20 Mi-8

NOTE

STANDS:

The stands are AVBL for parking of all class below ACFT and ACFT with smaller dimensions.

BAe-146, CRJ-100/200

STAND NR	LATITUDE	LONGITUDE
1 A		113 18 25.99E 113 18 31.80E